
NNN NNN EEEEEEEEEEEEEEE TTTTTTTTTTTTTTT AAAAAAAAA CCCCCCCCCCC PPPPPPPPPPP
NNN NNN EEEEEEEEEEEEEEE TTTTTTTTTTTTTTT AAAAAAAAA CCCCCCCCCCC PPPPPPPPPPP
NNN NNN EEEEEEEEEEEEEEE TTTTTTTTTTTTTTT AAAAAAAAA CCCCCCCCCCC PPPPPPPPPPP
NNN NNN EEE TTT AAA AAA CCC PPP PPP
NNN NNN EEE TTT AAA AAA CCC PPP PPP
NNN NNN EEE TTT AAA AAA CCC PPP PPP
NNNNNN NNN EEE TTT AAA AAA CCC PPP PPP
NNNNNN NNN EEE TTT AAA AAA CCC PPP PPP
NNNNNN NNN EEE TTT AAA AAA CCC PPP PPP
NNN NNN NNN EEEEEEEEEEE TTT AAA AAA CCC PPPPPPPPPPP
NNN NNN NNN EEEEEEEEEEE TTT AAA AAA CCC PPPPPPPPPPP
NNN NNN NNN EEEEEEEEEEE TTT AAA AAA CCC PPPPPPPPPPP
NNN NNNNNN EEE TTT AAAAAAAAAAAAAAA CCC PPP
NNN NNNNNN EEE TTT AAAAAAAAAAAAAAA CCC PPP
NNN NNNNNN EEE TTT AAAAAAAAAAAAAAA CCC PPP
NNN NNN EEE TTT AAA AAA CCC PPP
NNN NNN EEE TTT AAA AAA CCC PPP
NNN NNN EEE TTT AAA AAA CCC PPP
NNN NNN EEEEEEEEEEEEEEE TTT AAA AAA CCCCCCCCCCC PPP
NNN NNN EEEEEEEEEEEEEEE TTT AAA AAA CCCCCCCCCCC PPP
NNN NNN EEEEEEEEEEEEEEE TTT AAA AAA CCCCCCCCCCC PPP

FILEID**NSPMSGDEF

```
NN      NN    SSSSSSSS  PPPPPPPP    MM      MM    SSSSSSSS    GGGGGGGG  DDDDDDDD    EEEEEEEEEE  FFFFFFFFFF
NN      NN    SSSSSSSS  PPPPPPPP    MM      MM    SSSSSSSS    GGGGGGGG  DDDDDDDD    EEEEEEEEEE  FFFFFFFFFF
NN      NN  SS          PP      PP  MMMM  MMMM  SS          GG          DD      DD  EE          FF
NN      NN  SS          PP      PP  MMMM  MMMM  SS          GG          DD      DD  EE          FF
NNNN    NN  SS          PP      PP  MM  MM  MM  SS          GG          DD      DD  EE          FF
NNNN    NN  SS          PP      PP  MM  MM  MM  SS          GG          DD      DD  EE          FF
NN  NN  NN    SSSSSS    PPPPPPPP    MM      MM    SSSSSS    GG          DD      DD  EEEEEEEE    FFFFFFFF
NN  NN  NN    SSSSSS    PPPPPPPP    MM      MM    SSSSSS    GG          DD      DD  EEEEEEEE    FFFFFFFF
NN    NNNN          SS  PP          MM      MM          SS  GG  GGGGGG  DD      DD  EE          FF
NN    NNNN          SS  PP          MM      MM          SS  GG  GGGGGG  DD      DD  EE          FF
NN      NN          SS  PP          MM      MM          SS  GG      GG  DD      DD  EE          FF
NN      NN          SS  PP          MM      MM          SS  GG      GG  DD      DD  EE          FF
NN      NN  SSSSSSSS    PP          MM      MM  SSSSSSSS      GGGGGG    DDDDDDDD    EEEEEEEEEE  FF
NN      NN  SSSSSSSS    PP          MM      MM  SSSSSSSS      GGGGGG    DDDDDDDD    EEEEEEEEEE  FF

  SSSSSSSS  DDDDDDDD    LL
  SSSSSSSS  DDDDDDDD    LL
SS          DD      DD  LL
SS          DD      DD  LL
SS          DD      DD  LL
SS          DD      DD  LL
  SSSSSS    DD      DD  LL
  SSSSSS    DD      DD  LL
        SS  DD      DD  LL
        SS  DD      DD  LL
        SS  DD      DD  LL
        SS  DD      DD  LL
SSSSSSSS    DDDDDDDD    LLLLLLLLLL
SSSSSSSS    DDDDDDDD    LLLLLLLLLL
```

```
                MODULE  $nspmsgdef

;*
;*              NSPMSGDEF.SDL   - NSP and Transport Message Definitions
;*              Version 'V04-000'
;*
;*****************************************************************************
;*                                                                           *
;*  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY                                  *
;*  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.                   *
;*  ALL RIGHTS RESERVED.                                                     *
;*                                                                           *
;*  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED    *
;*  ONLY IN  ACCORDANCE WITH  THE  TERMS  OF  SUCH  LICENSE  AND WITH THE    *
;*  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR  ANY  OTHER    *
;*  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY    *
;*  OTHER PERSON.  NO TITLE TO AND OWNERSHIP OF  THE  SOFTWARE IS  HEREBY    *
;*  TRANSFERRED.                                                             *
;*                                                                           *
;*  THE INFORMATION IN THIS SOFTWARE IS  SUBJECT TO CHANGE WITHOUT NOTICE    *
;*  AND  SHOULD  NOT  BE  CONSTRUED AS  A COMMITMENT BY DIGITAL EQUIPMENT    *
;*  CORPORATION.                                                             *
;*                                                                           *
;*  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE  OR  RELIABILITY OF ITS    *
;*  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.                  *
;*                                                                           *
;*                                                                           *
;*****************************************************************************
;*
;*****************************************************************************
;*
;*  AUTHOR:             Alan D. Eldridge        1-April-1982
;*
;*  MODIFIED BY:
;*
;*      V03-005 RNG0004         Rod N. Gamache  19-Nov-1982
;*              Change ENDNODE format messages to LONG format
;*              messages. Change RTS bit definitions in LONG format
;*              messages to be in the flags byte, rather than the
;*              service class.
;*
;*      V03-004 RNG0003         Rod N. Gamache  11-Oct-1982
;*              Add Phase IV Level 2 router definitions
;*
;*      V03-C03 RNG0002         Rod N. Gamache  29-Sep-1982
;*              Add Phase IV endnode definitions
;*
;*      V03-001 RNG0001         Rod N. Gamache  14-Jul-1982
;*              Add Phase IV transport definitions
;*
```

```
{++
{
{  A thumbnail sketch of the NSP message formats is as follows:
{
{
{  <0eb0 0000><4b_LINK>{2b_ACK}<2b_SEG><DATA>                          DATA MSG
{  <0011 0000><4b_LINK>{2b_ACK}<2b_SEG><u16_DATA>                      INT. MSG
{  <0001 0000><4b_LINK>{2b_ACK}<2b_SEG><2b_FLOW>                       L.S. MSG
{
{  <0000 0100><4b_LINK><2b_ACK>                                        DATA ACK
{  <0001 0100><4b_LINK><2b_ACK>                                        OTH. ACK
{  <0010 0100><2b_DST>                                                 CA
{
{  <0001 1000><2k_0><2b_SRC><1b_SRV><1b_INFO><2b_SEGSIZ><CTL>          CI
{  <0010 1000><4b_LINK><1b_SRV><1b_INFO><2b_SEGSIZ><i16_DATA>          CC
{  <0011 1000><4b_LINK><2b_REA><i16_DATA>                              DI
{  <0100 1000><4b_LINK><2b_REA>                                        DC
{  <0100 1000><2b_DST><2k_0><2k_1>                                     CT
{  <0100 1000><4b_LINK><2k_42>                                         DT
{  <0100 1000><4b_LINK><2k_41>                                         NLT
{
{  <0101 1000>------                                                   START
{
{  <4b_LINK    ::=  <2b_DST><2b_SRC>              link address, not = 0
{  <2b_ACK     ::=  <1001><12 bit seg number>     if NAK
{                   <1000><12 bit seg number>     if ACK
{  <2b_SEG>    ::=  <0000><12 bit seg number>
{  <2b_FLOW>   ::=  <0000><2 bit subchannel><2 bit mode><1 byte count>
{                          0 => data          00 => no change
{                          1 => interrupt     01 => stop
{                                             10 => start
{
{  <1b_SRV>    ::=  <00000001>                    if no flow control
{                   <00000101>                    if segment flow control
{                   <00001001>                    if message flow control
{  <1b_INFO>   ::=  <00000001>                    if NSP V3.1
{                   <00000000>                    if NSP V3.2
{
{
{  <CTL>       ::=  <DNAME><SNAME><00vv00da><ACCOUNT><i16_DATA>
{                                          if a       if d
{                                  vv = Session control version
{                                   0 = Version 1.0
{                                       All other are reserved
{                    <DNAME> ::= <NAME>
{                    <SNAME> ::= <NAME>
{                    <NAME>  ::= <1k_0><1b_objtyp>  objtyp not= 0
{                                <1k_1><1k_0><i16_desc>
{                                <1k_2><1k_0><2b_gcod><2b_ucod><i12_desc>
{                    <ACCT>  ::= <i39_id><i39_psw><i39_acc>
{
{--
AGGREGATE  nspmsg  STRUCTURE  PREFIX nsp$ TAG $$;
    {
```

```
    {
    {  Define message codes -- first byte of message
    {
    {
    CONSTANT  msg_ci     EQUALS %x18 TAG c;      { Connect Initiate
    CONSTANT  msg_ca     EQUALS %x24 TAG c;      { Connect Acknowledge
    CONSTANT  msg_cc     EQUALS %x28 TAG c;      { Connect Confirm
    CONSTANT  msg_data   EQUALS %x00 TAG c;      { Data
    CONSTANT  msg_int    EQUALS %x30 TAG c;      { Interrupt
    CONSTANT  msg_ls     EQUALS %x10 TAG c;      { Link Service
    CONSTANT  msg_liack  EQUALS %x14 TAG c;      { LS/INT Ack
    CONSTANT  msg_dtack  EQUALS %x04 TAG c;      { Data ACK
    CONSTANT  msg_di     EQUALS %x38 TAG c;      { Disconnect Initiate
    CONSTANT  msg_dc     EQUALS %x48 TAG c;      { Disconnect Confirm
                                                 {
    {
    {
    {  Define maximum message header sizes
    {
    {
    CONSTANT  hsz_ci     EQUALS  240 TAG c;      {&Connect Initiate
    CONSTANT  hsz_ca     EQUALS    3 TAG c;      { Connect Acknowledge
    CONSTANT  hsz_cc     EQUALS  100 TAG c;      {&Connect Confirm
    CONSTANT  hsz_data   EQUALS    9 TAG c;      { Data
    CONSTANT  hsz_int    EQUALS    9 TAG c;      { Interrupt
    CONSTANT  hsz_ls     EQUALS    9 TAG c;      { Link Service
    CONSTANT  hsz_ack    EQUALS    7 TAG c;      { LS/INT or Data Ack
    CONSTANT  hsz_di     EQUALS   22 TAG c;      { Disconnect Initiate
    CONSTANT  hsz_dc     EQUALS   22 TAG c;      { Disconnect Confirm
    CONSTANT  hsz_cd     EQUALS  240 TAG c;      {&Maximum of all connect
                                                 {  or disconnect messages
                                                 {
    qual        UNION;                           { Miscellaneous message fields
                                                 {
      qual_msg      STRUCTURE TAG $$;            { Misc. MSG field qualifiers
        msg_sp1     BITFIELD  LENGTH 4;          { Skip constant part of field
        msg_li      BITFIELD  MASK;              { Set if not DATA subchannel msg
        msg_int     BITFIELD  MASK;              { Set if INT rather than LS msg
        dstlnk      WORD;                        { Destination link address
        srclnk      WORD;                        { Source link address
        END qual_msg;                            {
                                                 {
      qual_data     STRUCTURE TAG $$;            { Qualifiers to NSP$C_MSG_DATA
        data_sp     BITFIELD  LENGTH 5;          { Skip constant part of field
        data_bom    BITFIELD  MASK;              { Set if first seg in message
        data_eom    BITFIELD  MASK;              { Set if last seg in message
        data_ovfw   BITFIELD  MASK;              { Set if no further segs could
        END qual_data;                           {  be buffered without overflow
                                                 {  of the session ctl buffer -
                                                 {  INTERNAL ONLY, not in NSP
                                                 {
      qual_ack      STRUCTURE TAG $$;            { Qualifiers to all ACK fields
        ack_num     BITFIELD  MASK   LENGTH 12;  { Seg number being ACK'd
        ack_nak     BITFIELD  MASK;              { Set if this is a NAK
        ack_sp2     BITFIELD  LENGTH 2;          { Skip reserved field
        ack_valid   BITFIELD  MASK;              { Set to identify field as an
```

```
    END qual_ack;                                   {  ACK and not just a segment #
                                                    {
  qual_srv      STRUCTURE TAG $$;                   { Qualifiers to SERVICES field
                                                    { in CI and CC messages
    srv_01      BITFIELD  MASK   LENGTH 2;          { Must be value "01"
    srv_flw     BITFIELD  MASK   LENGTH 2;          { Receiver's flow control mode
    CONSTANT    srv_nfc   EQUALS 0 TAG c;           {  no flow control
    CONSTANT    srv_sfc   EQUALS 1 TAG c;           {  segment flow control
    CONSTANT    srv_mfc   EQUALS 2 TAG c;           {  message flow control
    srv_spl     BITFIELD  MASK   LENGTH 3;          { Reserved bits
    srv_ext     BITFIELD  MASK;                     { Set if field extends to next
                                                    { byte
    CONSTANT    srv_req   EQUALS %B11110011         { Mask of SERVICE bits which
                TAG m;                              { must have a know value
    CONSTANT    srv_req   EQUALS %B00000001         { ...that known value
                TAG c;
    END qual_srv;                                   {
                                                    {
  qual_inf      STRUCTURE TAG $$;                   { Qualifiers to INFO field in
                                                    { CI and CC messages
    inf_ver     BITFIELD  MASK   LENGTH 2;          { NSP version number
    CONSTANT    inf_v32   EQUALS 0 TAG c;           {  Version 3.2
    CONSTANT    inf_v31   EQUALS 1 TAG c;           {  Version 3.1
    CONSTANT    inf_v33   EQUALS 2 TAG c;           {  Version 3.3
                                                    {  "3" is reserved
    END qual_inf;                                   {
                                                    {
  qual_flw      STRUCTURE TAG $$;                   { Link Service message LSFLAGS
                                                    { field definition
    flw_mode    BITFIELD  MASK   LENGTH 2;          { Back-pressure value field
    CONSTANT    flw_nop   EQUALS 0 TAG c;           {  no-change
    CONSTANT    flw_xoff  EQUALS 1 TAG c;           {  stop flow
    CONSTANT    flw_xon   EQUALS 2 TAG c;           {  start flow
                                                    {  "3" is reserved
    flw_chan    BITFIELD  MASK   LENGTH 2;          { Sub channel selector
    CONSTANT    flw_data  EQUALS 0 TAG c;           {  Data subchannel
    CONSTANT    flw_int   EQUALS 1 TAG c;           {  Interrupt subchannel
                                                    {  "2" and "3" are reserved
    flw_drv     BITFIELD  MASK   LENGTH 4;          { Define the remainder of the
                                                    { field for Netdriver internal
                                                    { flags
    END qual_flw;                                   {
                                                    {
  qual_altflw   STRUCTURE TAG $$;                   { Alternate Link Service
                                                    { message LSFLAGS
    {
    {  These flags define the LSFLAGS in an alternate way to "qual_flw"
    {  above.  It depicts the same information, but takes advantage of
    {  the fact that not all values of the 2-bit fields are used and hence
    {  1-bit flags can be used rather than constants.
    {
    {  The first 4 bits are part of NSP.  The last 4 bits are Netdriver
    {  internal flags.
    {
    flw_xoff    BITFIELD  MASK   LENGTH 1;    { Stop flow on DATA subchannel
    flw_xon     BITFIELD  MASK   LENGTH 1;    { Start  "    "  "     "
```

```
        flw_lisub   BITFIELD  MASK   LENGTH 1;   { Flow control count is for the
                                                 { Link Service/Interrupt, and
                                                 { not the DATA, subchannel
        flw_sp1     BITFIELD  MASK   LENGTH 1;   { Spare
        flw_inuse   BITFIELD  MASK   LENGTH 1;   { XWB$B_X_FLW is in use
        flw_int     BITFIELD  MASK   LENGTH 1;   { XWB$B_X_FLW describes an
                                                 { "Interrupt", not a "Link-
                                                 {  Service", message
        flw_sp2     BITFIELD  MASK   LENGTH 1;   { Spare
        flw_sp3     BITFIELD  MASK   LENGTH 1;   { Spare
        END qual_altflw;                         {
    END qual;

END nspmsg ;
```

```
{
{
{  Phase III Routing Message Definitions
{
{
{  The following is a thumbnail sketch of the possibilities for the first byte
{  in a received message:
{
{
{       <0000 1000>     Phase II NOP
{       <0101 1000>     Phase II Start
{
{       <0100 xx10>     Phase II route header
{       <000x x010>     Phase III route header
{
{       <000x x010>     Phase IV non-broadcast circuit route header
{       <00xx 0x10>     Phase IV broadcast circuit route header
{
{       <0000 0001>     Phase III init
{       <0000 0011>     Phase III verification
{       <0000 0101>     Phase III hello message
{       <0000 0111>     Phase III routing message
{
{       <0000 1001>     Phase IV Level 2 routing message
{       <0000 1011>     Phase IV broadcast circuit Router hello message
{       <0000 1101>     Phase IV broadcast circuit Endnode hello message
{
{
{
AGGREGATE  tr3msg  STRUCTURE  PREFIX tr3$ TAG $$;
    {
    {
    {  Define message codes --  first byte of message  (DECnet calls these
    {                           "control flags")
    {
    {
    CONSTANT  msg_init  EQUALS %x01 TAG c;      { "Initialization" message
    CONSTANT  msg_verf  EQUALS %x03 TAG c;      { "Verification" message
    CONSTANT  msg_hello EQUALS %x05 TAG c;      { "Hello" message
    CONSTANT  msg_rout  EQUALS %x07 TAG c;      { "Routing" message
    CONSTANT  msg_data  EQUALS %x02 TAG c;      { Normal route-thru message
                                                {  (without qualifiers)
    CONSTANT  msg_str2  EQUALS %x58 TAG c;      { Phase II "Start" message
    CONSTANT  msg_nop2  EQUALS %x08 TAG c;      { Phase II "Nop" message

    {
    {
    {  Define message header sizes where applicable
    {
    {
    CONSTANT  hsz_data  EQUALS   6  TAG c;      { Normal route-thru message

    {
    {
    {  Define qualifiers to the various message codes
```

```
    {
    {
    qual        UNION;                          { Miscellaneous message fields

      qual_msg    STRUCTURE TAG $$;              { Common qualifiers
        msg_ctl   BITFIELD  MASK LENGTH 1;       { Set on Phase III control msgs
                                                 { - clear on all other messages
        msg_rth   BITFIELD  MASK LENGTH 1;       { Set if a Phase II or III
                                                 { route-header,  clear if a
                                                 { Phase II control message
        end qual_msg;                            {

      qual_rtflg  STRUCTURE TAG $$;              { Route-header qualifiers
        rtflg_012 BITFIELD        LENGTH 3;      { Must have the value 010
        rtflg_rqr BITFIELD  MASK LENGTH 1;       { Set if "return-to-sender" on
                                                 { error is requested
        rtflg_rts BITFIELD  MASK LENGTH 1;       { Set if message is being
                                                 { "returned-to-sender"
        rtflg_5   BITFIELD        LENGTH 1;      { Must be clear
        rtflg_ph2 BITFIELD  MASK LENGTH 1;       { Set if Phase II route-header
        rtflg_7   BITFIELD        LENGTH 1;      { Must be clear
        END qual_rtflg;

      END qual;

    END tr3msg;
```

```
{
{
{  Phase IV Routing Message Definitions
{
{  The following is a thumbnail sketch of the possibilities for the first byte
{  in a received message:
{
{       <000x x010>     Phase IV non-broadcast circuit route header
{       <00xx 0x10>     Phase IV broadcast circuit route header
{
{       <0000 1001>     Phase IV Level 2 routing message
{       <0000 1011>     Phase IV broadcast circuit Router hello message
{       <0000 1101>     Phase IV broadcast circuit Endnode hello message
{
{
AGGREGATE  tr4msg  STRUCTURE  PREFIX tr4$ TAG $$;
    {
    {
    {  Define message codes --  first byte of message  (DECnet calls these
    {                           "control flags")
    {
    {
    CONSTANT  msg_bcrhel EQUALS %xB TAG c;      { Broadcast Circuit Router
                                                {  "Hello" message
    CONSTANT  msg_bcehel EQUALS %xD TAG c;      { Broadcast Circuit Endnode
                                                {  "Hello" message
                                                {  (without qualifiers)
    CONSTANT  msg_rdata EQUALS %x02 TAG c;      { Normal route-thru message
    CONSTANT  msg_ldata EQUALS %x06 TAG c;      { Long header data message
    {
    {
    {  Define constants
    {
    {
    CONSTANT  T3MULT    EQUALS %x2 TAG c;       { T3 multiplier
    CONSTANT  BCT3MULT  EQUALS %x8 TAG c;       { Broadcast Circuit T3
                                                {  multiplier
    CONSTANT  VER_LOWW  EQUALS %x0002 TAG c;    { Transport's version number
    CONSTANT  VER_HIB   EQUALS %x00 TAG c;      {       V2.0.0
    CONSTANT  HIORD     EQUALS %x000400AA TAG c; { HIORD part of node address
    CONSTANT  RTR_LVL1  EQUALS %x2 TAG c;       { Level 1 router type code
    CONSTANT  RTR_LVL2  EQUALS %x1 TAG c;       { Level 2 router type code
    CONSTANT  END_NODE  EQUALS %x3 TAG c;       { Endnode type code
    CONSTANT  BCR_MID1  EQUALS %x030000AB TAG c; { Broadcast circuit router's
    CONSTANT  BCR_MID2  EQUALS %x0 TAG c;       {  multicast ID
    CONSTANT  BCE_MID1  EQUALS %x040000AB TAG c; { Broadcast circuit endnode's
    CONSTANT  BCE_MID2  EQUALS %x0 TAG c;       {  multicast ID
    CONSTANT  PRO_TYPE  EQUALS %x0360   TAG c;  { Transports protocol type


    {
    {
```

```
    {  Define message header sizes where applicable
    {
    {
    CONSTANT  hsz_data  EQUALS   21  TAG c;     { BC Endnode route-thru message

    {
    {
    {  Define qualifiers to message codes
    {
    {
    qual        UNION;                          { Miscellaneous message fields

      qual_rtflg  STRUCTURE TAG $$;             { Long Route-header
                                                {  qualifiers
        rtflg_01  BITFIELD       LENGTH 2;      { Must have the value 10
        rtflg_lng BITFIELD  MASK LENGTH 1;      { Set if Long format message
        rtflg_rqr BITFIELD  MASK LENGTH 1;      { Set if return-to-sender requested
        rtflg_rts BITFIELD  MASK LENGTH 1;      { Set if message is being
                                                { "returned-to-sender"
        rtflg_ini BITFIELD  MASK LENGTH 1;      { Set if Intra-NI message
                                                {  (on route-thru messages)
        rtflg_ver BITFIELD       LENGTH 2;      { Route header version number
        END qual_rtflg;

      qual_sclass  STRUCTURE TAG $$;            { Long format SERVICE CLASS
                                                {   qualifiers
        sclass_metr  BITFIELD       LENGTH 1;   { Metric - RESERVED
        sclass_1     BITFIELD       LENGTH 1;   { Must be clear - RESERVED
        sclass_ls    BITFIELD       LENGTH 1;   { Load splitting - RESERVED
        sclass_suba  BITFIELD       LENGTH 1;   { Sub Area - RESERVED
        sclass_bc    BITFIELD       LENGTH 1;   { Broadcast - RESERVED
        sclass_57    BITFIELD       LENGTH 3;   { Must be clear - RESERVED
        END qual_sclass;

       qual_addr   STRUCTURE TAG $$;            { Node address qualifiers
         addr_dest BITFIELD  MASK LENGTH 10;    { Destination address field
         addr_area BITFIELD  MASK LENGTH 6;     { Area part of node address
         END qual_addr;

       END qual;

     END tr4msg;

END_MODULE  $nspmsgdef ;
```

NETUSR
SDL

LIBTAIL
B32

XWBDEF
SDL

NETDEFS
MAR

PSIUSR
SDL

NETDRVMAC
MAR

NODRIVER
LIS

NSPMSGDEF
SDL

LIBHEAD
B32

NET
LIS

NETMACROS
MAR

NETACPTRN
LIS